

## 21.15 ODBC monitoring

### 21.15.1 Overview

ODBC monitoring corresponds to the *Database monitor* item type in the Zabbix frontend.

ODBC is a C programming language middle-ware API for accessing database management systems (DBMS). The ODBC concept was developed by Microsoft and later ported to other platforms.

Zabbix may query any database, which is supported by ODBC. To do that, Zabbix does not directly connect to the databases, but uses the ODBC interface and drivers set up in ODBC. This function allows for more efficient monitoring of different databases for multiple purposes - for example, checking specific database queues, usage statistics and so on. Zabbix supports unixODBC, which is one of the most commonly used open source ODBC API implementations.

### 21.15.2 Installing unixODBC

The suggested way of installing unixODBC is to use the Linux operating system default package repositories. In the most popular Linux distributions unixODBC is included in the package repository by default. If it's not available, it can be obtained at the unixODBC homepage:

<http://www.unixodbc.org/download.html>.

Installing unixODBC on RedHat/Fedora based systems using the *yum* package manager:

```
shell> yum -y install unixODBC unixODBC-devel
```

Installing unixODBC on SUSE based systems using the *zypper* package manager:

```
# zypper in unixODBC-devel
```

The unixODBC-devel package is needed to compile Zabbix with unixODBC support.

### 21.15.3 Installing unixODBC drivers

A unixODBC database driver should be installed for the database, which will be monitored. unixODBC has a list of supported databases and drivers: <http://www.unixodbc.org/drivers.html>. In some Linux distributions database drivers are included in package repositories. Installing MySQL database driver on RedHat/Fedora based systems using the *yum* package manager:

```
shell> yum install mysql-connector-odbc
```

Installing MySQL database driver on SUSE based systems using the *zypper* package manager:

```
zypper in MyODBC-unixODBC
```

## 21.15.4 Configuring unixODBC

ODBC configuration is done by editing the **odbcinst.ini** and **odbc.ini** files. To verify the configuration file location, type:

```
shell> odbcinst -j
```

**odbcinst.ini** is used to list the installed ODBC database drivers:

```
[mysql]
Description = ODBC for MySQL
Driver      = /usr/lib/libmyodbc5.so
```

Parameter details:

Attribute	Description
<i>mysql</i>	Database driver name.
<i>Description</i>	Database driver description.
<i>Driver</i>	Database driver library location.

**odbc.ini** is used to define data sources:

```
[test]
Description = MySQL test database
Driver      = mysql
Server     = 127.0.0.1
User       = root
Password   =
Port       = 3306
Database   = zabbix
```

Parameter details:

Attribute	Description
<i>test</i>	Data source name (DSN).
<i>Description</i>	Data source description.
<i>Driver</i>	Database driver name - as specified in odbcinst.ini
<i>Server</i>	Database server IP/DNS.
<i>User</i>	Database user for connection.
<i>Password</i>	Database user password.
<i>Port</i>	Database connection port.
<i>Database</i>	Database name.

To verify if ODBC connection is working successfully, a connection to database should be tested. That can be done with the **isql** utility (included in the unixODBC package):

```

shell> isql test
+-----+
| Connected!
|
| sql-statement
| help [tablename]
| quit
|
+-----+
SQL>

```

### 21.15.5 Compiling Zabbix with ODBC support

To enable ODBC support, Zabbix should be compiled with the following flag:

```
--with-unixodbc[=ARG] use odbc driver against unixODBC package
```

See more about Zabbix installation from the [source code](#).

### 21.15.6 Item configuration in Zabbix frontend

Configure a database monitoring [item](#):

Item

Name

Type

Key

User name

Password

SQL query 

select count (\*) from hosts

Type of information

Specifically for database monitoring items you must enter:

Type	Select <i>Database monitor</i> here.
Key	Enter <b>db.odbc.select</b> [unique_description,data_source_name] The unique description will serve to identify the item in triggers etc. The data source name (DSN) must be set as specified in <code>odbc.ini</code> .
User name	Enter the database user name (optional if user is specified in <code>odbc.ini</code> )
Password	Enter the database user password (optional if password is specified in <code>odbc.ini</code> )
SQL query	Enter the SQL query

