

massAdd()

Available since version: **1.8**

Parameters

multidimensional array with Hosts, Groups, Template, Macros data

Only host details can be added this way, not hosts themselves.

Parameter	Type	Optional	Description	Details
hosts	array		Host objects to update	
groups	array	Yes	Host group objects where hosts should be added.	
templates	array	Yes	Template objects which should be linked to hosts.	
macros	array	Yes	Macros objects which should be added to hosts.	

Returns

Parameter	Description
result	Operation successful. Result will contain array of updated Host IDs.
error	In case of any errors

Example

Add two macros to host with **ID** "100100000010092"

```
{
  "jsonrpc": "2.0",
  "method": "host.massAdd",
  "params": {
    "hosts": [
      {
        "hostid": "100100000010092"
      }
    ],
    "macros": [
      {
        "macro": "${TEST1}",
        "value": "MACROTEST1"
      },
      {
        "macro": "${TEST2}",
        "value": "MACROTEST2"
      }
    ]
  },
  "auth": "f223adf833b2bf2ff38574a67bba6372",
  "id": 2
}
```

```
}
```

Hosts updated successfully:

```
{  
  "jsonrpc": "2.0",  
  "result": {  
    "hostids": ["100100000010092"]  
  },  
  "id": 2  
}
```

From:

<https://www.zabbix.com/documentation/1.8/> - **Zabbix Documentation 1.8**

Permanent link:

<https://www.zabbix.com/documentation/1.8/api/host/massadd>

Last update: **2014/09/25 14:40**

