

create()

This function allows you to create a mediatype as defined by the **mediatype data** array.

Parameters

| Parameter | Type | Optional | Description | Details |
|-----------------------|------------------------|----------|---|---|
| mediatype data | <i>array or object</i> | | Array of Mediatype objects or a single object | mediatypeid shouldn't be specified |

Returns

| Parameter | Description |
|---------------|--|
| result | Operation successful. Result will contain array of created Mediatype IDs. mediatypeid are assigned to each Mediatype object |
| error | In case of any errors |

Example

Create two new mediatypes:

```
{
  "jsonrpc": "2.0",
  "method": "mediatype.create",
  "params": [{
    "type": "0",
    "description": "Root Email",
    "smtp_server": "rootmail@domain.com",
    "smtp_helo": "domain.com",
    "smtp_email": "domain@domain.com",
    "exec_path": "",
    "gsm_modem": "",
    "username": "",
    "passwd": ""
  },
  {
    "type": "2",
    "description": "SMS",
    "smtp_server": "",
    "smtp_helo": "",
    "smtp_email": "",
    "exec_path": "",
    "gsm_modem": "\\dev\\ttyS0",
    "username": "",
    "passwd": ""
  }
  ],
  "auth": "038e1d7b1735c6a5436ee9eae095879e",
  "id": 2
}
```

```
}
```

Mediatype created successfully:

```
{  
  "jsonrpc": "2.0",  
  "result": {  
    "mediatypeids": ["100100000214797", "100100000214798"]  
  },  
  "id": 2  
}
```

Mediatype already exists:

```
{  
  "jsonrpc": "2.0",  
  "error": {  
    "code": -32602,  
    "message": "Invalid params.",  
    "data": "[ CMediatype::create ] Cannot create Mediatype"  
  },  
  "id": 2  
}
```

From:

<https://www.zabbix.com/documentation/1.8/> - **Zabbix Documentation 1.8**

Permanent link:

<https://www.zabbix.com/documentation/1.8/api/mediatype/create>

Last update: **2019/01/28 14:45**

