

exists()

Available since version: **1.8.3**

This function allows you to check whether trigger with given trigger data exists.

Parameters

Parameter	Type	Optional	Description	Details
nodeids	<i>array</i>	yes	List of node IDs where to search for given item	
description	<i>string</i>	No	Trigger description	
expression	<i>string</i>	No	Trigger expression	
hostid	<i>string</i>	yes	Host ID	
host	<i>string</i>	yes	Host name	

Returns

Parameter	Description
result	Operation successful. Result will contain boolean variable.
error	In case of any errors

Example

Check if trigger with description "APC: System UPS Load" and expression "{TEST_hp3000:vfs.file.cksum[c:\config.sys].last(0)}=0" exists

```
{
  "jsonrpc": "2.0",
  "method": "trigger.exists",
  "params": {
    "host": "ZABBIX-Server",
    "description": "Apache is not running on {HOSTNAME}",
    "expression": "{ZABBIX-Server:proc_cnt[httpd].last(0)}<1"
  },
  "auth": "3a57200802b24cda67c4e4010b50c065",
  "id": 2
}
```

Trigger exists:

```
{
  "jsonrpc": "2.0",
  "result": true,
  "id": 2
}
```

From:

<https://www.zabbix.com/documentation/1.8/> - **Zabbix Documentation 1.8**

Permanent link:

<https://www.zabbix.com/documentation/1.8/api/trigger/exists>

Last update: **2014/09/25 14:40**

