

host.get

Description

integer/array `host.get(object parameters)`

The method allows to retrieve hosts according to the given parameters.

Parameters

(object) Parameters defining the desired output.

The method supports the following parameters.

Parameter	Type	Description
groupids	string/array	Return only hosts that belong to the given groups.
applicationids	string/array	Return only hosts that have the given applications.
dserviceids	string/array	Return only hosts that are related to the given discovered services.
graphids	string/array	Return only hosts that have the given graphs.
hostids	string/array	Return only hosts with the given host IDs.
httptestids	string/array	Return only hosts that have the given web checks.
interfaceids	string/array	Return only hosts that use the given interfaces.
itemids	string/array	Return only hosts that have the given items.
maintenanceids	string/array	Return only hosts that are affected by the given maintenances.
monitored_hosts	flag	Return only monitored hosts.
proxy_hosts	flag	Return only proxies.
proxyids	string/array	Return only hosts that are monitored by the given proxies.
templated_hosts	flag	Return both hosts and templates.
templateids	string/array	Return only hosts that are linked to the given templates.
triggerids	string/array	Return only hosts that have the given triggers.
with_items	flag	Return only hosts that have items. Overrides the <code>with_monitored_items</code> , <code>with_historical_items</code> and <code>with_simple_graph_items</code> parameters.
with_applications	flag	Return only hosts that have applications.
with_graphs	flag	Return only hosts that have graphs.
with_historical_items	flag	Return only hosts that have enabled or not supported items with historical data. Overrides the <code>with_simple_graph_items</code> parameter.
with_httptests	flag	Return only hosts that have web checks. Overrides the <code>with_monitored_httptests</code> parameter.
with_monitored_httptests	flag	Return only hosts that have enabled web checks.

Parameter	Type	Description
with_monitored_items	flag	Return only hosts that have enabled items. Overrides the with_historical_items and with_simple_graph_items parameters.
with_monitored_triggers	flag	Return only hosts that have enabled triggers. All of the items used in the trigger must also be enabled.
with_simple_graph_items	flag	Return only hosts that have items with numeric type of information.
with_triggers	flag	Return only hosts that have triggers. Overrides the with_monitored_triggers parameter.
withInventory	flag	Return only hosts that have inventory data.
selectGroups	query	Return the host groups that the host belongs to in the groups property. Does not support shorten or arrays of properties.
selectApplications	query	Return the applications from the host in the applications property. Supports count; does not support shorten.
selectDiscoveries	query	Return the low level discoveries from the host in the discoveries property. Supports count; does not support shorten.
selectGraphs	query	Return the graphs from the host in the graphs property. Supports count; does not support shorten.
selectInterfaces	query	Return the host interfaces in the interfaces property. Supports count; does not support shorten.
selectInventory	boolean/array	Return the host inventory from the host in the inventory property. Possible values are true to return all of the data, or an array of property names to return only specific properties.
selectItems	query	Return the items from the host in the items property. Supports count; does not support shorten.
selectMacros	query	Return the macros from the host in the macros property. Does not support shorten or arrays of properties.
selectParentTemplates	query	Return the templates that the host is linked to in the parentTemplates property. Supports count; does not support shorten.
selectScreens	query	Return the screens from the host in the screens property. Supports count; does not support shorten.
selectTriggers	query	Return the triggers from the host in the triggers property. Supports count; does not support shorten.

Parameter	Type	Description
filter	object	Return only those results that exactly match the given filter. Accepts an array, where the keys are property names, and the values are either a single value or an array of values to match against. Allows filtering by interface properties.
limitSelects	integer	Limits the number of records returned by subselects. Applies to the following subselects: selectParentTemplates - results will be sorted by host; selectInterfaces; selectItems - sorted by name; selectDiscoveries - sorted by name; selectTriggers - sorted by description; selectGraphs - sorted by name; selectApplications - sorted by name; selectScreens - sorted by name.
search	object	Return results that match the given wildcard search. Accepts an array, where the keys are property names, and the values are strings to search for. If no additional options are given, this will perform a LIKE “%...%” search. Allows searching by interface properties. Works only with text fields.
sortfield	string/array	Sort the result by the given properties. Possible values are: hostid, host, name, status.
countOutput	flag	These parameters being common for all get methods are described in detail on the Generic Zabbix API information page.
editable	boolean	
excludeSearch	flag	
limit	integer	
nodeids	string/array	
output	query	
preservekeys	flag	
search	object	
searchByAny	boolean	
searchWildcardsEnabled	boolean	
sortorder	string/array	
startSearch	flag	

Return values

(integer/array) Returns either:

- an array of objects;
- the count of retrieved objects, if the countOutput parameter has been used.

Examples

Retrieving data by name

Retrieve all data about two hosts named "Zabbix server" and "Linux server".

Request:

```
{
  "jsonrpc": "2.0",
  "method": "host.get",
  "params": {
    "output": "extend",
    "filter": {
      "host": [
        "Zabbix server",
        "Linux server"
      ]
    }
  },
  "auth": "038e1d7b1735c6a5436ee9eae095879e",
  "id": 1
}
```

Response:

```
{
  "jsonrpc": "2.0",
  "result": [
    {
      "maintenances": [],
      "hostid": "10160",
      "proxy_hostid": "0",
      "host": "Zabbix server",
      "status": "0",
      "disable_until": "0",
      "error": "",
      "available": "0",
      "errors_from": "0",
      "lastaccess": "0",
      "ipmi_authtype": "-1",
      "ipmi_privilege": "2",
      "ipmi_username": "",
      "ipmi_password": "",
      "ipmi_disable_until": "0",
      "ipmi_available": "0",
      "snmp_disable_until": "0",
      "snmp_available": "0",
      "maintenanceid": "0",
    }
  ]
}
```

```
    "maintenance_status": "0",
    "maintenance_type": "0",
    "maintenance_from": "0",
    "ipmi_errors_from": "0",
    "snmp_errors_from": "0",
    "ipmi_error": "",
    "snmp_error": "",
    "jmx_disable_until": "0",
    "jmx_available": "0",
    "jmx_errors_from": "0",
    "jmx_error": "",
    "name": "Zabbix server"
  },
  {
    "maintenances": [],
    "hostid": "10167",
    "proxy_hostid": "0",
    "host": "Linux server",
    "status": "0",
    "disable_until": "0",
    "error": "",
    "available": "0",
    "errors_from": "0",
    "lastaccess": "0",
    "ipmi_authtype": "-1",
    "ipmi_privilege": "2",
    "ipmi_username": "",
    "ipmi_password": "",
    "ipmi_disable_until": "0",
    "ipmi_available": "0",
    "snmp_disable_until": "0",
    "snmp_available": "0",
    "maintenanceid": "0",
    "maintenance_status": "0",
    "maintenance_type": "0",
    "maintenance_from": "0",
    "ipmi_errors_from": "0",
    "snmp_errors_from": "0",
    "ipmi_error": "",
    "snmp_error": "",
    "jmx_disable_until": "0",
    "jmx_available": "0",
    "jmx_errors_from": "0",
    "jmx_error": "",
    "name": "Linux server"
  }
],
  "id": 1
}
```

Retrieving host groups

Retrieve names of the groups host "Zabbix server" is member of, but no host details themselves.

Request:

```
{
  "jsonrpc": "2.0",
  "method": "host.get",
  "params": {
    "output": ["hostid"],
    "selectGroups": "extend",
    "filter": {
      "host": [
        "Zabbix server"
      ]
    }
  },
  "auth": "038e1d7b1735c6a5436ee9eae095879e",
  "id": 2
}
```

Response:

```
{
  "jsonrpc": "2.0",
  "result": [
    {
      "groups": [
        {
          "groupid": "2",
          "name": "Linux servers",
          "internal": "0"
        },
        {
          "groupid": "4",
          "name": "Zabbix servers",
          "internal": "0"
        }
      ],
      "hostid": "10085"
    }
  ],
  "id": 2
}
```

Retrieving linked templates

Retrieve the IDs and names of templates linked to host "10084".

Request:

```
{
  "jsonrpc": "2.0",
  "method": "host.get",
  "params": {
    "output": ["hostid"],
    "selectParentTemplates": [
      "templateid",
      "name"
    ],
    "hostids": "10084"
  },
  "id": 1,
  "auth": "70785d2b494a7302309b48afcdb3a401"
}
```

Response:

```
{
  "jsonrpc": "2.0",
  "result": [
    {
      "parentTemplates": [
        {
          "name": "Template OS Linux",
          "templateid": "10001"
        },
        {
          "name": "Template App Zabbix Server",
          "templateid": "10047"
        }
      ],
      "hostid": "10084"
    }
  ],
  "id": 1
}
```

See also

- [Host group](#)
- [Template](#)
- [User macro](#)
- [Host interface](#)

Source

CHost::get() in *frontends/php/api/classes/CHost.php*.

From:

<https://www.zabbix.com/documentation/2.0/> - **Zabbix Documentation 2.0**

Permanent link:

<https://www.zabbix.com/documentation/2.0/manual/appendix/api/host/get>

Last update: **2019/01/28 14:49**

