

## > Proxy object

The following objects are directly related to the proxy API.

### Proxy

The proxy object has the following properties.

Property	Type	Description
proxyid	string	<i>(readonly)</i> ID of the proxy.
<b>host</b> (required)	string	Name of the proxy.
<b>status</b> (required)	integer	Type of proxy. Possible values: 5 - active proxy; 6 - passive proxy.
lastaccess	timestamp	<i>(readonly)</i> Time when the proxy last connected to the server.

### Proxy interface

The proxy interface object defines the interface used to connect to a passive proxy. It has the following properties.

Property	Type	Description
interfaceid	string	<i>(readonly)</i> ID of the interface.
<b>dns</b> (required)	string	DNS name to connect to. Can be empty if connections are made via IP address.
<b>ip</b> (required)	string	IP address to connect to. Can be empty if connections are made via DNS names.
<b>port</b> (required)	string	Port number to connect to.
<b>useip</b> (required)	integer	Whether the connection should be made via IP address. Possible values are: 0 - connect using DNS name; 1 - connect using IP address.
hostid	string	<i>(readonly)</i> ID of the proxy the interface belongs to.

From:

<https://www.zabbix.com/documentation/2.0/> - **Zabbix Documentation 2.0**

Permanent link:

<https://www.zabbix.com/documentation/2.0/manual/appendix/api/proxy/definitions>

Last update: **2014/09/25 14:42**

