

> User object

The following objects are directly related to the user API.

User

The user object has the following properties.

Property	Type	Description
userid	string	<i>(readonly)</i> ID of the user.
alias <i>(required)</i>	string	User alias.
attempt_clock	timestamp	<i>(readonly)</i> Time of the last unsuccessful login attempt.
attempt_failed	integer	<i>(readonly)</i> Recent failed login attempt count.
attempt_ip	string	<i>(readonly)</i> IP address from where the last unsuccessful login attempt came from.
autologin	integer	Whether to enable auto-login. Possible values: 0 - <i>(default)</i> auto-login disabled; 1 - auto-login enabled.
autologout	integer	User session life time in seconds. If set to 0, the session will never expire. Default: 900.
lang	string	Language code of the user's language. Default: en_GB.
name	string	Name of the user.
refresh	integer	Automatic refresh period in seconds. Default: 30.
rows_per_page	integer	Amount of object rows to show per page. Default: 50.
surname	string	Surname of the user.
theme	string	User's theme. Possible values: default - <i>(default)</i> system default; classic - Classic; originalblue - Original blue; darkblue - Black & Blue; darkorange - Dark orange.
type	integer	Type of the user. Possible values: 1 - <i>(default)</i> Zabbix user; 2 - Zabbix admin; 3 - Zabbix super admin.

Property	Type	Description
url	string	URL of the page to redirect the user to after logging in.

From:
<https://www.zabbix.com/documentation/2.0/> - **Zabbix Documentation 2.0**

Permanent link:
<https://www.zabbix.com/documentation/2.0/manual/appendix/api/user/definitions>

Last update: **2014/11/11 22:01**

