

## > Media object

The following objects are directly related to the usermedia API.

### Media

Media are created, updated and deleted via the the [user API](#).

The media object defines how a media type should be used for a user. It has the following properties.

Property	Type	Description
mediaid	string	( <i>readonly</i> ) ID of the media.
<b>active</b> (required)	integer	Whether the media is enabled.  Possible values: 0 - enabled; 1 - disabled.
<b>mediatypeid</b> (required)	string	ID of the media type used by the media.
<b>period</b> (required)	string	Time when the notifications can be sent as a <a href="#">time period</a> .
<b>sendto</b> (required)	string	Address, user name or other identifier of the recipient.
<b>severity</b> (required)	integer	Trigger severities to send notifications about.  Severities are stored in binary form with each bit representing the corresponding severity. For example, 12 equals 1100 in binary and means, that notifications will be sent from triggers with severities warning and average.  Refer to the <a href="#">trigger object page</a> for a list of supported trigger severities.
<b>userid</b> (required)	string	ID of the user that uses the media.

From:

<https://www.zabbix.com/documentation/2.0/> - **Zabbix Documentation 2.0**

Permanent link:

<https://www.zabbix.com/documentation/2.0/manual/appendix/api/usermedia/definitions>

Last update: **2014/09/26 11:29**

