

# application.exists

## Description

boolean application.exists(object **filter**)

This method checks if at least one application that matches the given filter criteria exists.

## Parameters

(object) Criteria to search by.

The following parameters are supported as search criteria.

Parameter	Type	Description
hostid	string/array	IDs of the hosts the applications must belong to.
name	string/array	Names of the applications
node	string	Name of the node the applications must belong to. This will override the nodeids parameter.
nodeids	string/array	ID of the node the applications must belong to.

## Return values

(boolean) Returns true if at least one application that matches the given filter criteria exists.

## Examples

### Check application on host

Check if application "Memory" exists on host "10084."

Request:

```
{
  "jsonrpc": "2.0",
  "method": "application.exists",
  "params": {
    "hostid": "10084",
    "name": "Memory"
  },
  "auth": "3a57200802b24cda67c4e4010b50c065",
  "id": 1
}
```

## Response:

```
{  
  "jsonrpc": "2.0",  
  "result": true,  
  "id": 1  
}
```

## Source

CApplication::exists() in *frontends/php/api/classes/CApplication.php*.

From:  
<https://www.zabbix.com/documentation/2.2/> - **Zabbix Documentation 2.2**

Permanent link:  
<https://www.zabbix.com/documentation/2.2/manual/api/reference/application/exists>

Last update: **2019/01/28 14:49**

