

> Trigger prototype object

The following objects are directly related to the `triggerprototype` API.

Trigger

The trigger prototype object has the following properties.

Property	Type	Description
<code>triggerid</code>	string	(<i>readonly</i>) ID of the trigger prototype.
description (required)	string	Name of the trigger prototype.
expression (required)	string	Reduced trigger expression.
<code>comments</code>	string	Additional comments to the trigger prototype.
<code>priority</code>	integer	Severity of the trigger prototype. Possible values: 0 - (<i>default</i>) not classified; 1 - information; 2 - warning; 3 - average; 4 - high; 5 - disaster.
<code>status</code>	integer	Whether the trigger prototype is enabled or disabled. Possible values: 0 - (<i>default</i>) enabled; 1 - disabled.
<code>templateid</code>	string	(<i>readonly</i>) ID of the parent template trigger prototype.
<code>type</code>	integer	Whether the trigger prototype can generate multiple problem events. Possible values: 0 - (<i>default</i>) do not generate multiple events; 1 - generate multiple events.
<code>url</code>	string	URL associated with the trigger prototype.

From:

<https://www.zabbix.com/documentation/2.2/> - **Zabbix Documentation 2.2**

Permanent link:

<https://www.zabbix.com/documentation/2.2/manual/api/reference/triggerprototype/object>

Last update: **2014/09/25 14:41**

