

graph.create

Description

object graph.create(object/array **graphs**)

This method allows to create new graphs.

Parameters

(object/array) Graphs to create.

Additionally to the [standard graph properties](#), the method accepts the following parameters.

Parameter	Type	Description
gitems (required)	array	Graph items to be created for the graph.

Return values

(object) Returns an object containing the IDs of the created graphs under the `graphids` property. The order of the returned IDs matches the order of the passed graphs.

Examples

Creating a graph

Create a graph with two items.

Request:

```
{
  "jsonrpc": "2.0",
  "method": "graph.create",
  "params": {
    "name": "MySQL bandwidth",
    "width": 900,
    "height": 200,
    "gitems": [
      {
        "itemid": "22828",
        "color": "00AA00",
        "sortorder": "0"
      },
      {
        "itemid": "22829",
```

```
        "color": "3333FF",  
        "sortorder": "1"  
    }  
  ],  
  "auth": "038e1d7b1735c6a5436ee9eae095879e",  
  "id": 1  
}
```

Response:

```
{  
  "jsonrpc": "2.0",  
  "result": {  
    "graphids": [  
      "652"  
    ]  
  },  
  "id": 1  
}
```

See also

- [Graph item](#)

Source

CGraph::create() in *frontends/php/include/classes/api/services/CGraph.php*.

From:

<https://www.zabbix.com/documentation/2.4/> - **Zabbix Documentation 2.4**

Permanent link:

<https://www.zabbix.com/documentation/2.4/manual/api/reference/graph/create>

Last update: **2019/01/28 14:49**

