

> Proxy object

The following objects are directly related to the proxy API.

Proxy

The proxy object has the following properties.

Property	Type	Description
proxyid	string	<i>(readonly)</i> ID of the proxy.
host (required)	string	Name of the proxy.
status (required)	integer	Type of proxy. Possible values: 5 - active proxy; 6 - passive proxy.
description	text	Description of the proxy.
lastaccess	timestamp	<i>(readonly)</i> Time when the proxy last connected to the server.

Proxy interface

The proxy interface object defines the interface used to connect to a passive proxy. It has the following properties.

Property	Type	Description
interfaceid	string	<i>(readonly)</i> ID of the interface.
dns (required)	string	DNS name to connect to. Can be empty if connections are made via IP address.
ip (required)	string	IP address to connect to. Can be empty if connections are made via DNS names.
port (required)	string	Port number to connect to.
useip (required)	integer	Whether the connection should be made via IP address. Possible values are: 0 - connect using DNS name; 1 - connect using IP address.
hostid	string	<i>(readonly)</i> ID of the proxy the interface belongs to.

From:
<https://www.zabbix.com/documentation/2.4/> - **Zabbix Documentation 2.4**

Permanent link:
<https://www.zabbix.com/documentation/2.4/manual/api/reference/proxy/object>

Last update: **2014/09/25 14:43**



