

user.update

Description

object user.update(object/array **users**)

This method allows to update existing users.

Parameters

(object/array) User properties to be updated.

The `userid` property must be defined for each user, all other properties are optional. Only the passed properties will be updated, all others will remain unchanged.

Additionally to the [standard user properties](#), the method accepts the following parameters.

Parameter	Type	Description
passwd	string	User's password.
usrgrps	array	User groups to replace existing user groups. The user groups must have the <code>usrgrp_id</code> property defined.

Return values

(object) Returns an object containing the IDs of the updated users under the `user_ids` property.

Examples

Renaming a user

Rename a user to John Doe.

Request:

```
{
  "jsonrpc": "2.0",
  "method": "user.update",
  "params": {
    "userid": "1",
    "name": "John",
    "surname": "Doe"
  },
  "auth": "038e1d7b1735c6a5436ee9eae095879e",
  "id": 1
}
```

```
}
```

Response:

```
{  
  "jsonrpc": "2.0",  
  "result": {  
    "userids": [  
      "1"  
    ]  
  },  
  "id": 1  
}
```

See also

- [user.updateprofile](#)

Source

CUser::update() in *frontends/php/include/classes/api/services/CUser.php*.

From:

<https://www.zabbix.com/documentation/2.4/> - **Zabbix Documentation 2.4**

Permanent link:

<https://www.zabbix.com/documentation/2.4/manual/api/reference/user/update>

Last update: **2019/01/28 14:49**

