

## Zabbix API changes in 3.0

### 3.0.24

#### **dservice**

Bug fixes:

[ZBX-14833](#) dservice.get: fixed “selectHosts” option to return correct hosts that are monitored by current proxy or server

### 3.0.16

#### **maintenance**

Bug fixes:

[ZBX-6167](#) maintenance.update: fixed partial updating

### 3.0.15

#### **maintenance**

Bug fixes:

[ZBX-12991](#) maintenance.create: removed default values for “active\_since” and “active\_till” fields

### 3.0.14

#### **alert**

Bug fixes:

[ZBX-12655](#) alert.get: fixed method to return only personal alerts and alerts sent to users within the same user group.

### 3.0.12

#### **host**

Bug fixes:

[ZBX-10754](#) host.update, host.massupdate: fixed inheritance of template properties in web scenarios.

## template

Bug fixes:

[ZBX-10754](#) template.update, template.massupdate: fixed inheritance of template properties in web scenarios.

## 3.0.11

### map

Bug fixes:

[ZBX-12768](#) map.create, map.update: added url field validation of map and map elements. Valid URI scheme list is defined in [ZBX\\_URI\\_VALID\\_SCHEMES](#).

### screen item

Bug fixes:

[ZBX-12768](#) screenitem.create, screenitem.update: added url field validation. Valid URI scheme list is defined in [ZBX\\_URI\\_VALID\\_SCHEMES](#).

### trigger

Bug fixes:

[ZBX-12768](#) trigger.create, trigger.update: added url field validation. Valid URI scheme list is defined in [ZBX\\_URI\\_VALID\\_SCHEMES](#).

### trigger prototype

Bug fixes:

[ZBX-12768](#) triggerprototype.create, triggerprototype.update: added url field validation. Valid URI scheme list is defined in [ZBX\\_URI\\_VALID\\_SCHEMES](#).

### user

Bug fixes:

[ZBX-12768](#) user.create, user.update: added url field validation. Valid URI scheme list is defined in [ZBX\\_URI\\_VALID\\_SCHEMES](#).

## 3.0.6

## General

Bug fixes:

[ZBX-11244](#) fixed decoding a valid JSON-RPC request when PHP is compiled without JSON library

## httptest

Bug fixes:

[ZBX-11191](#) httptest.update: fixed web scenarios not properly updating step items when giving only applicationid and steps with httpstepid properties

[ZBX-11191](#) httptest.update: fixed updating templated web scenario steps by prohibiting to directly change the step name or giving different amount of steps than in template

[ZBX-11191](#) httptest.update: added mandatory field check in step validation

[ZBX-10842](#) httptest.update: fixed SQL error when updating httptest with applicationid and without httpstepid parameters

[ZBX-10842](#) httptest.update: prevented disappearing of step items when updating httptest without applicationid, httpstepid parameters

[ZBX-10842](#) httptest.update: fixed connecting web scenario applicationid to created steps when updating

## usergroup

Bug fixes:

[ZBX-11121](#) usergroup.update, usergroup.massupdate, usergroup.delete: disallowed leaving a user without linked user groups

## 3.0.5

### host

Bug fixes:

[ZBX-11151](#) implemented a dynamic default sort order for graph items; now the default sort order increases by one with each entry of a graph item

[ZBX-11020](#) host.create: made both "inventory" and "inventory\_mode" optional

## 3.0.4

### General

Bug fixes:

[ZBX-10880](#) fixed support of sending several Request objects at the same time to JSON-RPC

## hostprototype

Bug fixes:

[ZBX-9455](#) hostprototype.create, hostprototype.update: fixed length limit for host prototype name

### 3.0.3

## configuration

Bug fixes:

[ZBX-10752](#) configuration.export: fixed array formatting in exported JSON

[ZBX-10607](#) configuration.import: fixed validation of import in JSON format

[ZBX-10693](#) configuration.import: fixed importing template and/or host with trigger prototype dependency

## host

Bug fixes:

[ZBX-10587](#) host.create: fixed inventory mode not being inherited for host prototypes when linking a template to this host

## item

Bug fixes:

[ZBX-10755](#) item.delete: fixed possible SQL errors when deleting items which are used in Y axis MIN/MAX parameters

## template

Bug fixes:

[ZBX-10587](#) template.create: fixed inventory mode not being inherited for host prototypes when linking this template to another template or host

### 3.0.2

## General

Bug fixes:

[ZBX-9700](#) fixed API receiving requests without parameters and now showing a proper error message

## hostgroup

Bug fixes:

[ZBX-9162](#) hostgroup.get: performance improvements under MySQL

## httptest

Bug fixes:

[ZBX-10316](#) removed faulty web scenario step name validation

## item

Bug fixes:

[ZBX-10262](#) item.update: fixed "delta" field being modified for templated items

## maintenance

Bug fixes:

[ZBX-4842](#) maintenance.create, maintenance.update, maintenance.delete: added auditlog

[ZBX-10563](#) maintenance.create, maintenance.update: improved validation to disallow saving maintenance without timeperiods

## screen

Bug fixes:

[ZBX-10517](#) screen.update: fixed unexpected errors if changing the position of screen elements between screen cells

[ZBX-10517](#) screen.create, screen.update: added validation of vsize and hsize parameters

[ZBX-10369](#) screen.update: fixed unexpected deleting of screen items when updating both screen size and screen items

## triggerprototype

Bug fixes:

[ZBX-10155](#) triggerprototype.create, triggerprototype.update: prohibited creation of a trigger prototype without item prototypes in the expression

From:

<https://www.zabbix.com/documentation/3.0/> - **Zabbix Documentation 3.0**

Permanent link:

[https://www.zabbix.com/documentation/3.0/manual/api/changes\\_3.0](https://www.zabbix.com/documentation/3.0/manual/api/changes_3.0)

Last update: **2018/11/06 15:17**

