

# valuemap.create

## Description

object `valuemap.create(object/array valuemaps)`

This method allows to create new value maps.

## Parameters

(object/array) Value maps to create.

The method accepts value maps with with the [standard value map properties](#).

## Return values

(object) Returns an object containing the IDs of the created value maps the `valuemapids` property. The order of the returned IDs matches the order of the passed value maps.

## Examples

### Creating a value map

Create one value map with two mappings.

Request:

```
{
  "jsonrpc": "2.0",
  "method": "valuemap.create",
  "params": {
    "name": "Service state",
    "mappings": [
      {
        "value": "0",
        "newvalue": "Down"
      },
      {
        "value": "1",
        "newvalue": "Up"
      }
    ]
  },
  "auth": "57562fd409b3b3b9a4d916d45207bbcb",
  "id": 1
}
```

```
}
```

## Response:

```
{  
  "jsonrpc": "2.0",  
  "result": {  
    "valuemapids": [  
      "1"  
    ]  
  },  
  "id": 1  
}
```

## Source

CValueMap::create() in *frontends/php/include/classes/api/services/CValueMap.php*.

From:

<https://www.zabbix.com/documentation/3.0/> - **Zabbix Documentation 3.0**

Permanent link:

<https://www.zabbix.com/documentation/3.0/manual/api/reference/valuemap/create>

Last update: **2019/01/28 14:49**

