

iconmap.create

Description

object iconmap.create(object/array **iconMaps**)

This method allows to create new icon maps.

Parameters

(object/array) Icon maps to create.

Additionally to the [standard icon map properties](#), the method accepts the following parameters.

Parameter	Type	Description
mappings (required)	array	Icon mappings to be created for the icon map.

Return values

(object) Returns an object containing the IDs of the created icon maps under the `iconmapids` property. The order of the returned IDs matches the order of the passed icon maps.

Examples

Create an icon map

Create an icon map to display hosts of different types.

Request:

```
{
  "jsonrpc": "2.0",
  "method": "iconmap.create",
  "params": {
    "name": "Type icons",
    "default_iconid": "2",
    "mappings": [
      {
        "inventory_link": 1,
        "expression": "server",
        "iconid": "3"
      },
      {
        "inventory_link": 1,
        "expression": "switch",

```

```
        "iconid": "4"
      }
    ]
  },
  "auth": "038e1d7b1735c6a5436ee9eae095879e",
  "id": 1
}
```

Response:

```
{
  "jsonrpc": "2.0",
  "result": {
    "iconmapids": [
      "2"
    ]
  },
  "id": 1
}
```

See also

- [Icon mapping](#)

Source

`ClconMap::create()` in *frontends/php/include/classes/api/services/ClconMap.php*.

From: <https://www.zabbix.com/documentation/3.2/> - **Zabbix Documentation 3.2**

Permanent link: <https://www.zabbix.com/documentation/3.2/manual/api/reference/iconmap/create?rev=1447744884>

Last update: **2016/02/16 15:25**

