

iconmap.get

Description

integer/array iconmap.get(object **parameters**)

The method allows to retrieve icon maps according to the given parameters.

Parameters

(object) Parameters defining the desired output.

The method supports the following parameters.

| Parameter | Type | Description |
|------------------------|--------------|---|
| iconmapids | string/array | Return only icon maps with the given IDs. |
| sysmapids | string/array | Return only icon maps that are used in the given maps. |
| selectMappings | query | Return used icon mappings in the mappings property. |
| sortfield | string/array | Sort the result by the given properties. Possible values are: iconmapid and name. |
| countOutput | flag | These parameters being common for all get methods are described in detail in the reference commentary . |
| editable | boolean | |
| excludeSearch | flag | |
| filter | object | |
| limit | integer | |
| output | query | |
| preservekeys | flag | |
| search | object | |
| searchByAny | boolean | |
| searchWildcardsEnabled | boolean | |
| sortorder | string/array | |
| startSearch | flag | |

Return values

(integer/array) Returns either:

- an array of objects;
- the count of retrieved objects, if the countOutput parameter has been used.

Examples

Retrieve an icon map

Retrieve all data about icon map "3".

Request:

```
{
  "jsonrpc": "2.0",
  "method": "iconmap.get",
  "params": {
    "iconmapids": "3",
    "output": "extend",
    "selectMappings": "extend"
  },
  "auth": "038e1d7b1735c6a5436ee9eae095879e",
  "id": 1
}
```

Response:

```
{
  "jsonrpc": "2.0",
  "result": [
    {
      "mappings": [
        {
          "iconmappingid": "3",
          "iconmapid": "3",
          "iconid": "6",
          "inventory_link": "1",
          "expression": "server",
          "sortorder": "0"
        },
        {
          "iconmappingid": "4",
          "iconmapid": "3",
          "iconid": "10",
          "inventory_link": "1",
          "expression": "switch",
          "sortorder": "1"
        }
      ],
      "iconmapid": "3",
      "name": "Host type icons",
      "default_iconid": "2"
    }
  ],
  "id": 1
}
```

See also

- [Icon mapping](#)

Source

ClconMap::get() in *frontends/php/include/classes/api/services/ClconMap.php*.

From:

<https://www.zabbix.com/documentation/3.2/> - **Zabbix Documentation 3.2**

Permanent link:

<https://www.zabbix.com/documentation/3.2/manual/api/reference/iconmap/get>

Last update: **2019/01/28 14:50**

