

12 Upgrade notes for 3.2.2

Changed syntax for selecting nested host groups

Along with extended [nested host group](#) support, the syntax for including nested subgroups has changed.

In Zabbix 3.2.0 and 3.2.1 nested host groups are included with the parent host group, if the parent group is specified as `hostgroup/*`. In Zabbix 3.2.2, the `/*` syntax is dropped. Instead, nested host groups are included if simply the parent host group is specified as is. This means that a host group that is set, for example, in action conditions, now **silently** includes all its nested host groups.

Frontend changes

- The link for adding descriptions to triggers created by low-level discovery has been removed from *Monitoring* → *Triggers*. Such descriptions were later deleted anyway by low-level discovery, if they were not present in the original trigger prototype.

Daemon changes

- Active agent auto-registration events are not generated any more if there is no action for auto registration.

Miscellaneous changes

- Zabbix server and frontend now try to set the MySQL autocommit variable to “`autocommit=1`” (enable MySQL autocommit mode) at the beginning of each connection to the database. Failing to do so results in failed database connection.

From:

<https://www.zabbix.com/documentation/3.2/> - **Zabbix Documentation 3.2**

Permanent link:

https://www.zabbix.com/documentation/3.2/manual/installation/upgrade_notes_322

Last update: **2018/11/30 06:23**

