

## > Icon map object

The following objects are directly related to the `iconmap` API.

### Icon map

The icon map object has the following properties.

Property	Type	Description
<code>iconmapid</code>	string	<i>(readonly)</i> ID of the icon map.
<b>default_iconid</b> (required)	string	ID of the default icon.
<b>name</b> (required)	string	Name of the icon map.

### Icon mapping

The icon mapping object defines a specific icon to be used for hosts with a certain inventory field value. It has the following properties.

Property	Type	Description
<code>iconmappingid</code>	string	<i>(readonly)</i> ID of the icon map.
<b>iconid</b> (required)	string	ID of the icon used by the icon mapping.
<b>expression</b> (required)	string	Expression to match the inventory field against.
<b>inventory_link</b> (required)	integer	ID of the host inventory field. Refer to the <a href="#">host inventory object</a> for a list of supported inventory fields.
<code>iconmapid</code>	string	<i>(readonly)</i> ID of the icon map that the icon mapping belongs to.
<code>sortorder</code>	integer	<i>(readonly)</i> Position of the icon mapping in the icon map.

From:

<https://www.zabbix.com/documentation/3.4/> - **Zabbix Documentation 3.4**

Permanent link:

<https://www.zabbix.com/documentation/3.4/manual/api/reference/iconmap/object>

Last update: **2016/12/28 07:28**

