

# user.create

## Description

object user.create(object/array **users**)

This method allows to create new users.

## Parameters

(object/array) Users to create.

Additionally to the [standard user properties](#), the method accepts the following parameters.

Parameter	Type	Description
<b>passwd</b> (required)	string	User's password.
<b>usrgrps</b> (required)	array	User groups to add the user to. The user groups must have the <code>usrgrpid</code> property defined.
user_medias	array	Medias to create for the user.

## Return values

(object) Returns an object containing the IDs of the created users under the `userids` property. The order of the returned IDs matches the order of the passed users.

## Examples

### Creating a user

Create a new user, add him to a user group and create a new media for him.

Request:

```
{
  "jsonrpc": "2.0",
  "method": "user.create",
  "params": {
    "alias": "John",
    "passwd": "Doe123",
    "usrgrps": [
      {
        "usrgrpid": "7"
      }
    ]
  },
}
```

```
    "user_medias": [
      {
        "mediatypeid": "1",
        "sendto": "support@company.com",
        "active": 0,
        "severity": 63,
        "period": "1-7,00:00-24:00"
      }
    ],
    "auth": "038e1d7b1735c6a5436ee9eae095879e",
    "id": 1
  }
```

Response:

```
{
  "jsonrpc": "2.0",
  "result": {
    "userids": [
      "12"
    ]
  },
  "id": 1
}
```

## See also

- [Media](#)
- [User group](#)

## Source

CUser::create() in *frontends/php/include/classes/api/services/CUser.php*.

From:

<https://www.zabbix.com/documentation/3.4/> - **Zabbix Documentation 3.4**

Permanent link:

<https://www.zabbix.com/documentation/3.4/manual/api/reference/user/create>

Last update: **2019/01/28 14:50**

