

# trigger.adddependencies

## Description说明

object trigger.adddependencies(object/array **triggerDependencies**)

This method allows to create new trigger dependencies此方法允许创建新的触发器依赖关系。

## Parameters参数

(object/array) Trigger dependencies to create触发依赖关系创建。

Each trigger dependency has the following parameters每个触发器依赖关系具有以下参数：

Parameter参数	Type类型	Description说明
<b>triggerid</b> (required)	string	ID of the dependent trigger依赖触发器的ID.
<b>dependsOnTriggerid</b> (required)	string	ID of the trigger that the trigger depends on触发依赖的触发器的ID.

## Return values返回值

(object) Returns an object containing the IDs of the dependent triggers under the **triggerids** property. (object)返回一个对象，该对象包含**triggerids**属性下的依赖触发器的ID[]

## Examples范例

### Add a trigger dependency添加触发器依赖关系

Make trigger “14092” dependent on trigger “13565.” 触发器 “14092” 依赖于触发器 “13565.” 。

Request请求：

```
{
  "jsonrpc": "2.0",
  "method": "trigger.adddependencies",
  "params": {
    "triggerid": "14092",
    "dependsOnTriggerid": "13565"
  },
  "auth": "038e1d7b1735c6a5436ee9eae095879e",
  "id": 1
}
```

Response响应：

```
{
  "jsonrpc": "2.0",
  "result": {
    "triggerids": [
      "14092"
    ]
  },
  "id": 1
}
```

## See also参考

- [trigger.update](#)

## Source来源

CTrigger::addDependencies() in *frontends/php/include/classes/api/services/CTrigger.php*.

From: <https://www.zabbix.com/documentation/3.4/> - **Zabbix Documentation 3.4**

Permanent link: <https://www.zabbix.com/documentation/3.4/zh/manual/api/reference/trigger/adddependencies>

Last update: **2019/01/28 14:50**

