

## Zabbix API changes in 4.0

### 4.0.13

#### valuemap

Changes:

[ZBX-3783](#) `valuemap.get`: added strict validation of input parameters

### 4.0.8

#### alert

Changes:

[ZBX-11272](#) `alert.get`: added support of two new options `mediatypeid` and `sendto` in the `sortfield` parameter

### 4.0.7

#### discoveryrule

Bug fixes:

[ZBX-10861](#) `discoveryrule.create`, `discoveryrule.update`: changed “username” and “password” fields to optional for HTTP agent type discovery rules and using authentication

#### httptest

Bug fixes:

[ZBX-10861](#) `httptest.create`, `httptest.update`: changed “http\_user” and “http\_password” fields to optional when using authentication

#### item

Bug fixes:

[ZBX-10861](#) `item.create`, `item.update`: changed “username” and “password” fields to optional for HTTP agent type items and using authentication

#### itemprototype

Bug fixes:

[ZBX-10861](#) `itemprototype.create`, `itemprototype.update`: changed “username” and

“password” fields to optional for HTTP agent type item prototypes and using authentication

## 4.0.2

### dservice

Bug fixes:

[ZBX-14833](#) dservice.get: fixed “selectHosts” option to return correct hosts that are monitored by current proxy or server

From:

<https://www.zabbix.com/documentation/4.0/> - **Zabbix Documentation 4.0**

Permanent link:

[https://www.zabbix.com/documentation/4.0/manual/api/changes\\_4.0](https://www.zabbix.com/documentation/4.0/manual/api/changes_4.0)

Last update: **2019/09/03 06:44**

