

# application.delete

## 说明

object application.delete(array **applicationIds**)

此方法用于删除应用集。

## 参数

(array) 需要去删除的应用集 ID

## 返回值

(object) 返回一个“applicationid”属性下的要删除的应用程序 ID 的对象。

## 范例

### 删除多个应用集

删除两个应用集

请求:

```
{
  "jsonrpc": "2.0",
  "method": "application.delete",
  "params": [
    "356",
    "358"
  ],
  "auth": "3a57200802b24cda67c4e4010b50c065",
  "id": 1
}
```

响应:

```
{
  "jsonrpc": "2.0",
  "result": {
    "applicationids": [
      "356",
      "358"
    ]
  },
}
```

```
"id": 1  
}
```

## 来源

CApplication::delete() in *frontends/php/include/classes/api/services/CApplication.php*.

## Description

object application.delete(array **applicationIds**)

This method allows to delete applications.

## Parameters

(array) IDs of the applications to delete.

## Return values

(object) Returns an object containing the IDs of the deleted applications under the `applicationids` property.

## Examples

### Deleting multiple applications

Delete two applications.

Request:

```
{  
  "jsonrpc": "2.0",  
  "method": "application.delete",  
  "params": [  
    "356",  
    "358"  
  ],  
  "auth": "3a57200802b24cda67c4e4010b50c065",  
  "id": 1  
}
```

Response:

```
{
  "jsonrpc": "2.0",
  "result": {
    "applicationids": [
      "356",
      "358"
    ]
  },
  "id": 1
}
```

## Source

CApplication::delete() in *frontends/php/include/classes/api/services/CApplication.php*.

From:

<https://www.zabbix.com/documentation/4.0/> - **Zabbix Documentation 4.0**

Permanent link:

<https://www.zabbix.com/documentation/4.0/zh/manual/api/reference/application/delete>

Last update: **2019/01/28 14:50**

