

Man page of ZABBIX_PROXY

ZABBIX_PROXY

Section: Maintenance Commands (8)

Updated: 2018-10-11

[Index](#) [Return to Main Contents](#)

NAME

`zabbix_proxy` - Zabbix proxy daemon

SYNOPSIS

```
zabbix_proxy [-c config-file]  
zabbix_proxy [-c config-file] -R runtime-option  
zabbix_proxy -h  
zabbix_proxy -V
```

DESCRIPTION

`zabbix_proxy` is a daemon that collects monitoring data from devices and sends it to Zabbix server.

OPTIONS

- c, --config** *config-file*
Use the alternate *config-file* instead of the default one.
- f, --foreground**
Run Zabbix proxy in foreground.
- R, --runtime-control** *runtime-option*
Perform administrative functions according to *runtime-option*.

Runtime control options

`config_cache_reload`

Reload configuration cache. Ignored if cache is being currently loaded. Active Zabbix proxy will connect to the Zabbix server and request configuration data. Default configuration file (unless -c option is specified) will be used to find PID file and signal will be

sent to process, listed in PID file.

housekeeper_execute

Execute the housekeeper. Ignored if housekeeper is being currently executed.

log_level_increase[=*target*]

Increase log level, affects all processes if target is not specified

log_level_decrease[=*target*]

Decrease log level, affects all processes if target is not specified

Log level control targets

process-type

All processes of specified type (configuration syncer, data sender, discoverer, heartbeat sender, history syncer, housekeeper, http poller, icmp pinger, ipmi manager, ipmi poller, java poller, poller, self-monitoring, snmp trapper, task manager, trapper, unreachable poller, vmware collector)

process-type,N

Process type and number (e.g., poller,3)

pid

Process identifier, up to 65535. For larger values specify target as "process-type,N"

-h, --help

Display this help and exit.

-V, --version

Output version information and exit.

FILES

/usr/local/etc/zabbix_proxy.conf

Default location of Zabbix proxy configuration file (if not modified during compile time).

SEE ALSO

[zabbix_agentd\(8\)](#), [zabbix_get\(8\)](#), [zabbix_sender\(8\)](#),
[zabbix_server\(8\)](#)

AUTHOR

Alexei Vladishev <alex@zabbix.com>

Index

NAME

SYNOPSIS

DESCRIPTION

OPTIONS

FILES

SEE ALSO

AUTHOR

This document was created by [man2html](#), using the manual pages.

Time: 15:28:13 GMT, October 18, 2018

From:

<https://www.zabbix.com/documentation/4.2/> - Zabbix Documentation 4.2

Permanent link:

https://www.zabbix.com/documentation/4.2/manpages/zabbix_proxy

Last update: **2019/04/04 07:57**

