

hostinterface.update

Description

object `hostinterface.update(object/array hostInterfaces)`

This method allows to update existing host interfaces.

Parameters

(object/array) [Host interface properties](#) to be updated.

The `interfaceid` property must be defined for each host interface, all other properties are optional. Only the given properties will be updated, all others will remain unchanged.

Return values

(object) Returns an object containing the IDs of the updated host interfaces under the `interfaceids` property.

Examples

Changing a host interface port

Change the port of a host interface.

Request:

```
{
  "jsonrpc": "2.0",
  "method": "hostinterface.update",
  "params": {
    "interfaceid": "30048",
    "port": "30050"
  },
  "auth": "038e1d7b1735c6a5436ee9eae095879e",
  "id": 1
}
```

Response:

```
{
  "jsonrpc": "2.0",
  "result": {
```

```
    "interfaceids": [  
        "30048"  
    ],  
    "id": 1  
}
```

Source

CHostInterface::update() in *frontends/php/include/classes/api/services/CHostInterface.php*.

From:

<https://www.zabbix.com/documentation/4.2/> - **Zabbix Documentation 4.2**

Permanent link:

<https://www.zabbix.com/documentation/4.2/manual/api/reference/hostinterface/update>

Last update: **2019/01/28 14:51**

