

# iconmap.update

## Description

object iconmap.update(object/array **iconMaps**)

This method allows to update existing icon maps.

## Parameters

(object/array) Icon map properties to be updated.

The `iconmapid` property must be defined for each icon map, all other properties are optional. Only the passed properties will be updated, all others will remain unchanged.

Additionally to the [standard icon map properties](#), the method accepts the following parameters.

Parameter	Type	Description
mappings	array	Icon mappings to replace the existing icon mappings.

## Return values

(object) Returns an object containing the IDs of the updated icon maps under the `iconmapids` property.

## Examples

### Rename icon map

Rename an icon map to "OS icons".

Request:

```
{
  "jsonrpc": "2.0",
  "method": "iconmap.update",
  "params": {
    "iconmapid": "1",
    "name": "OS icons"
  },
  "auth": "038e1d7b1735c6a5436ee9eae095879e",
  "id": 1
}
```

Response:

```
{
  "jsonrpc": "2.0",
  "result": {
    "iconmapids": [
      "1"
    ]
  },
  "id": 1
}
```

## See also

- [Icon mapping](#)

## Source

`ClconMap::update()` in *frontends/php/include/classes/api/services/ClconMap.php*.

From: <https://www.zabbix.com/documentation/4.2/> - **Zabbix Documentation 4.2**

Permanent link: <https://www.zabbix.com/documentation/4.2/manual/api/reference/iconmap/update?rev=1447744970>

Last update: **2018/10/01 09:42**

