

mediatype.get

Description

integer/array mediatype.get(object **parameters**)

The method allows to retrieve media types according to the given parameters.

Parameters

(object) Parameters defining the desired output.

The method supports the following parameters.

Parameter	Type	Description
mediatypeids	string/array	Return only media types with the given IDs.
mediaids	string/array	Return only media types used by the given media.
userid	string/array	Return only media types used by the given users.
selectUsers	query	Return the users that use the media type in the users property.
sortfield	string/array	Sort the result by the given properties. Possible values are: mediatypeid.
countOutput	flag	These parameters being common for all get methods are described in detail in the reference commentary .
editable	boolean	
excludeSearch	flag	
filter	object	
limit	integer	
output	query	
preservekeys	flag	
search	object	
searchByAny	boolean	
searchWildcardsEnabled	boolean	
sortorder	string/array	
startSearch	flag	

Return values

(integer/array) Returns either:

- an array of objects;
- the count of retrieved objects, if the countOutput parameter has been used.

Examples

Retrieving media types

Retrieve all configured media types.

Request:

```
{
  "jsonrpc": "2.0",
  "method": "mediatype.get",
  "params": {
    "output": "extend"
  },
  "auth": "038e1d7b1735c6a5436ee9eae095879e",
  "id": 1
}
```

Response:

```
{
  "jsonrpc": "2.0",
  "result": [
    {
      "mediatypeid": "1",
      "type": "0",
      "description": "Email",
      "smtp_server": "mail.company.com",
      "smtp_helo": "company.com",
      "smtp_email": "zabbix@company.com",
      "exec_path": "",
      "gsm_modem": "",
      "username": "",
      "passwd": "",
      "status": "0"
    },
    {
      "mediatypeid": "2",
      "type": "3",
      "description": "Jabber",
      "smtp_server": "",
      "smtp_helo": "",
      "smtp_email": "",
      "exec_path": "",
      "gsm_modem": "",
      "username": "jabber@company.com",
      "passwd": "zabbix",
    }
  ]
}
```

```
    "status": "0"
  },
  {
    "mediatypeid": "3",
    "type": "2",
    "description": "SMS",
    "smtp_server": "",
    "smtp_helo": "",
    "smtp_email": "",
    "exec_path": "",
    "gsm_modem": "/dev/ttyS0",
    "username": "",
    "passwd": "",
    "status": "0"
  }
],
"id": 1
}
```

See also

- [User](#)

Source

CMediaType::get() in *frontends/php/api/classes/CMediaType.php*.

From:
<https://www.zabbix.com/documentation/4.2/> - **Zabbix Documentation 4.2**

Permanent link:
<https://www.zabbix.com/documentation/4.2/manual/api/reference/mediatype/get?rev=1411730602>

Last update: **2018/10/01 09:42**

