

# usermacro.create

## Description

object usermacro.create(object/array **hostMacros**)

This method allows to create new host macros.

## Parameters

(object/array) Host macros to create.

The method accepts host macros with the [standard host macro properties](#).

## Return values

(object) Returns an object containing the IDs of the created host macros under the `hostmacroids` property. The order of the returned IDs matches the order of the passed host macros.

## Examples

### Creating a host macro

Creat a host macro “`{SNMP_COMMUNITY}`” with the value “public” on host “10198”.

Request:

```
{
  "jsonrpc": "2.0",
  "method": "usermacro.create",
  "params": {
    "hostid": "10198",
    "macro": "{SNMP_COMMUNITY}",
    "value": "public"
  },
  "auth": "038e1d7b1735c6a5436ee9eae095879e",
  "id": 1
}
```

Response:

```
{
  "jsonrpc": "2.0",
  "result": {
```

```
    "hostmacroids": [  
        "11"  
    ],  
    "id": 1  
}
```

## Source

CUserMacro::create() in *frontends/php/include/classes/api/services/CUserMacro.php*.

From:

<https://www.zabbix.com/documentation/4.4/> - **Zabbix Documentation 4.4**

Permanent link:

<https://www.zabbix.com/documentation/4.4/manual/api/reference/usermacro/create>

Last update: **2019/04/02 06:04**

