

> Trigger prototype object

The following objects are directly related to the `triggerprototype` API.

Trigger prototype

The trigger prototype object has the following properties.

Property	Type	Description
<code>triggerid</code>	string	(<i>readonly</i>) ID of the trigger prototype.
description (required)	string	Name of the trigger prototype.
expression (required)	string	Reduced trigger expression.
<code>opdata</code>	string	Operational data.
<code>comments</code>	string	Additional comments to the trigger prototype.
<code>priority</code>	integer	Severity of the trigger prototype. Possible values: 0 - (<i>default</i>) not classified; 1 - information; 2 - warning; 3 - average; 4 - high; 5 - disaster.
<code>status</code>	integer	Whether the trigger prototype is enabled or disabled. Possible values: 0 - (<i>default</i>) enabled; 1 - disabled.
<code>templateid</code>	string	(<i>readonly</i>) ID of the parent template trigger prototype.
<code>type</code>	integer	Whether the trigger prototype can generate multiple problem events. Possible values: 0 - (<i>default</i>) do not generate multiple events; 1 - generate multiple events.
<code>url</code>	string	URL associated with the trigger prototype.
<code>recovery_mode</code>	integer	OK event generation mode. Possible values are: 0 - (<i>default</i>) Expression; 1 - Recovery expression; 2 - None.
<code>recovery_expression</code>	string	Reduced trigger recovery expression.
<code>correlation_mode</code>	integer	OK event closes. Possible values are: 0 - (<i>default</i>) All problems; 1 - All problems if tag values match.
<code>correlation_tag</code>	string	Tag for matching.

Property	Type	Description
manual_close	integer	Allow manual close. Possible values are: 0 - (default) No; 1 - Yes.
discover	integer	Trigger prototype discovery status. Possible values: 0 - (default) new triggers will be discovered; 1 - new triggers will not be discovered and existing triggers will be marked as lost.

Trigger prototype tag

The trigger prototype tag object has the following properties.

Property	Type	Description
tag (required)	string	Trigger prototype tag name.
value	string	Trigger prototype tag value.

From: <https://www.zabbix.com/documentation/5.2/> - **Zabbix Documentation 5.2**

Permanent link: <https://www.zabbix.com/documentation/5.2/manual/api/reference/triggerprototype/object>

Last update: **2020/05/20 09:33**

