

Man page of ZABBIX\_GET

# ZABBIX\_GET

Section: User Commands (1)

Updated: 2018-10-11

[Index](#) [Return to Main Contents](#)

---

## NAME

`zabbix_get` - Zabbix get utility

## SYNOPSIS

**zabbix\_get -s** *host-name-or-IP* [-**p** *port-number*] [-**I** *IP-address*] -**k** *item-key*

**zabbix\_get -s** *host-name-or-IP* [-**p** *port-number*] [-**I** *IP-address*] --**tls-connect** **cert** --**tls-ca-file** *CA-file* [--**tls-crl-file** *CRL-file*] [--**tls-agent-cert-issuer** *cert-issuer*] [--**tls-agent-cert-subject** *cert-subject*] --**tls-cert-file** *cert-file* --**tls-key-file** *key-file* -**k** *item-key*

**zabbix\_get -s** *host-name-or-IP* [-**p** *port-number*] [-**I** *IP-address*] --**tls-connect** **psk** --**tls-psk-identity** *PSK-identity* --**tls-psk-file** *PSK-file* -**k** *item-key*

**zabbix\_get -h**

**zabbix\_get -V**

## DESCRIPTION

**zabbix\_get** is a command line utility for getting data from Zabbix agent.

## OPTIONS

-**s**, --**host** *host-name-or-IP*

Specify host name or IP address of a host.

-**p**, --**port** *port-number*

Specify port number of agent running on the host. Default is 10050.

-**I**, --**source-address** *IP-address*

Specify source IP address.

-**k**, --**key** *item-key*

Specify key of item to retrieve value for.

--**tls-connect** *value*

How to connect to agent. Values:

## unencrypted

## **connect without encryption (default)**

### **psk**

**connect using TLS and a pre-shared key**

### **cert**

**connect using TLS and a certificate**

**--tls-ca-file *CA-file***

Full pathname of a file containing the top-level CA(s) certificates for peer certificate verification.

**--tls-crl-file *CRL-file***

Full pathname of a file containing revoked certificates.

**--tls-agent-cert-issuer *cert-issuer***

Allowed agent certificate issuer.

**--tls-agent-cert-subject *cert-subject***

Allowed agent certificate subject.

**--tls-cert-file *cert-file***

Full pathname of a file containing the certificate or certificate chain.

**--tls-key-file *key-file***

Full pathname of a file containing the private key.

**--tls-psk-identity *PSK-identity***

PSK-identity string.

**--tls-psk-file *PSK-file***

Full pathname of a file containing the pre-shared key.

**-h, --help**

Display this help and exit.

**-V, --version**

Output version information and exit.

## EXAMPLES

```
zabbix_get -s 127.0.0.1 -p 10050 -k "system.cpu.load[all,avg1]"
zabbix_get -s 127.0.0.1 -p 10050 -k "system.cpu.load[all,avg1]" --tls-connect
cert --tls-ca-file /home/zabbix/zabbix_ca_file --tls-agent-cert-issuer
"CN=Signing CA,OU=IT operations,O=Example Corp,DC=example,DC=com" --
tls-agent-cert-subject "CN=server1,OU=IT operations,O=Example
Corp,DC=example,DC=com" --tls-cert-file /home/zabbix/zabbix_get.crt --tls-
key-file /home/zabbix/zabbix_get.key
zabbix_get -s 127.0.0.1 -p 10050 -k "system.cpu.load[all,avg1]" --tls-connect
psk --tls-psk-identity "PSK ID Zabbix agentd" --tls-psk-file
/home/zabbix/zabbix_agentd.psk
```

## SEE ALSO

[zabbix\\_agentd\(8\)](#), [zabbix\\_proxy\(8\)](#), [zabbix\\_sender\(8\)](#), [zabbix\\_server\(8\)](#)

## AUTHOR

Alexei Vladishev <[alex@zabbix.com](mailto:alex@zabbix.com)>

---

## Index

[NAME](#)

[SYNOPSIS](#)

[DESCRIPTION](#)

[OPTIONS](#)

[EXAMPLES](#)

[SEE ALSO](#)

[AUTHOR](#)

---

This document was created by [man2html](#), using the manual pages.  
Time: 15:28:13 GMT, October 18, 2018

From:

<https://www.zabbix.com/documentation/current/> - **Zabbix Documentation 5.0**

Permanent link:

[https://www.zabbix.com/documentation/current/manpages/zabbix\\_get?rev=1539947228](https://www.zabbix.com/documentation/current/manpages/zabbix_get?rev=1539947228)

Last update: **2019/10/07 06:35**

