

discoveryrule.copy

Description

object `discoveryrule.copy(object parameters)`

This method allows to copy LLD rules with all of the prototypes to the given hosts.

Parameters

(object) Parameters defining the LLD rules to copy and the target hosts.

| Parameter | Type | Description |
|---------------------------|-------|--|
| <code>discoveryids</code> | array | IDs of the LLD rules to be copied. |
| <code>hostids</code> | array | IDs of the hosts to copy the LLD rules to. |

Return values

(boolean) Returns `true` if the copying was successful.

Examples

Copy an LLD rule to multiple hosts

Copy an LLD rule to two hosts.

Request:

```
{
  "jsonrpc": "2.0",
  "method": "discoveryrule.copy",
  "params": {
    "discoveryids": [
      "27426"
    ],
    "hostids": [
      "10196",
      "10197"
    ]
  },
  "auth": "038e1d7b1735c6a5436ee9eae095879e",
  "id": 1
}
```

Response:

```
{  
  "jsonrpc": "2.0",  
  "result": true,  
  "id": 1  
}
```

Source

CDiscoveryrule::copy() in *ui/include/classes/api/services/CDiscoveryRule.php*.

From:

<https://www.zabbix.com/documentation/current/> - **Zabbix Documentation 5.0**

Permanent link:

<https://www.zabbix.com/documentation/current/manual/api/reference/discoveryrule/copy>

Last update: **2020/08/21 12:30**

