

discoveryrule.copy

Description

object `discoveryrule.copy(object parameters)`

This method allows to copy LLD rules with all of the prototypes to the given hosts.

Parameters

(object) Parameters defining the LLD rules to copy and the target hosts.

Parameter	Type	Description
<code>discoveryids</code>	array	IDs of the LLD rules to be copied.
<code>hostids</code>	array	IDs of the hosts to copy the LLD rules to.

Return values

(boolean) Returns `true` if the copying was successful.

Examples

Copy an LLD rule to multiple hosts

Copy an LLD rule to two hosts.

Request:

```
{
  "jsonrpc": "2.0",
  "method": "discoveryrule.copy",
  "params": {
    "discoveryids": [
      "27426"
    ],
    "hostids": [
      "10196",
      "10197"
    ]
  },
  "auth": "038e1d7b1735c6a5436ee9eae095879e",
  "id": 1
}
```

Response:

```
{  
  "jsonrpc": "2.0",  
  "result": true,  
  "id": 1  
}
```

Source

CDiscoveryrule::copy() in *frontends/php/include/classes/api/services/CDiscoveryRule.php*.

From: <https://www.zabbix.com/documentation/current/> - **Zabbix Documentation 5.0**

Permanent link: <https://www.zabbix.com/documentation/current/manual/api/reference/discoveryrule/copy?rev=1570430125>

Last update: **2019/10/07 06:35**

