

# drule.update

## Description

object drule.update(object/array **discoveryRules**)

This method allows to update existing discovery rules.

## Parameters

(object/array) Discovery rule properties to be updated.

The `druleid` property must be defined for each discovery rule, all other properties are optional. Only the passed properties will be updated, all others will remain unchanged.

Additionally to the [standard discovery rule properties](#), the method accepts the following parameters.

Parameter	Type	Description
dchecks	array	Discovery <a href="#">checks</a> to replace existing checks.

## Return values

(object) Returns an object containing the IDs of the updated discovery rules under the `druleids` property.

## Examples

### Change the IP range of a discovery rule

Change the IP range of a discovery rule to "192.168.2.1-255".

Request:

```
{
  "jsonrpc": "2.0",
  "method": "drule.update",
  "params": {
    "druleid": "6",
    "iprange": "192.168.2.1-255"
  },
  "auth": "038e1d7b1735c6a5436ee9eae095879e",
  "id": 1
}
```

Response:

```
{
  "jsonrpc": "2.0",
  "result": {
    "druleids": [
      "6"
    ]
  },
  "id": 1
}
```

## See also

- [Discovery check](#)

## Source

CDRule::update() in *ui/include/classes/api/services/CDRule.php*.

From:  
<https://www.zabbix.com/documentation/current/> - **Zabbix Documentation 5.0**

Permanent link:  
<https://www.zabbix.com/documentation/current/manual/api/reference/drule/update>

Last update: **2020/05/05 11:09**

