

host.massremove

Description

object `host.massremove(object parameters)`

This method allows to remove related objects from multiple hosts.

Parameters

(object) Parameters containing the IDs of the hosts to update and the objects that should be removed.

| Parameter | Type | Description |
|------------------------------|--------------|---|
| hostids (required) | string/array | IDs of the hosts to be updated. |
| groupids | string/array | Host groups to remove the given hosts from. |
| interfaces | object/array | Host interfaces to remove from the given hosts. The host interface object must have the <code>ip</code> , <code>dns</code> and <code>port</code> properties defined. |
| macros | string/array | User macros to delete from the given hosts. |
| templateids | string/array | Templates to unlink from the given hosts. |
| templateids_clear | string/array | Templates to unlink and clear from the given hosts. |

Return values

(object) Returns an object containing the IDs of the updated hosts under the `hostids` property.

Examples

Unlinking templates

Unlink a template from two hosts and delete all of the templated entities.

Request:

```
{
  "jsonrpc": "2.0",
  "method": "host.massremove",
  "params": {
    "hostids": ["69665", "69666"],
    "templateids_clear": "325"
  },
  "auth": "038e1d7b1735c6a5436ee9eae095879e",
}
```

```
"id": 1  
}
```

Response:

```
{  
  "jsonrpc": "2.0",  
  "result": {  
    "hostids": [  
      "69665",  
      "69666"  
    ]  
  },  
  "id": 1  
}
```

See also

- [host.update](#)
- [User macro](#)
- [Host interface](#)

Source

`CHost::massRemove()` in `ui/include/classes/api/services/CHost.php`.

From: <https://www.zabbix.com/documentation/current/> - **Zabbix Documentation 5.0**

Permanent link: <https://www.zabbix.com/documentation/current/manual/api/reference/host/massremove>

Last update: **2020/05/05 10:17**

