

iconmap.update

Description

object iconmap.update(object/array **iconMaps**)

This method allows to update existing icon maps.

Parameters

(object/array) Icon map properties to be updated.

The `iconmapid` property must be defined for each icon map, all other properties are optional. Only the passed properties will be updated, all others will remain unchanged.

Additionally to the [standard icon map properties](#), the method accepts the following parameters.

Parameter	Type	Description
mappings	array	Icon mappings to replace the existing icon mappings.

Return values

(object) Returns an object containing the IDs of the updated icon maps under the `iconmapids` property.

Examples

Rename icon map

Rename an icon map to "OS icons".

Request:

```
{
  "jsonrpc": "2.0",
  "method": "iconmap.update",
  "params": {
    "iconmapid": "1",
    "name": "OS icons"
  },
  "auth": "038e1d7b1735c6a5436ee9eae095879e",
  "id": 1
}
```

Response:

```
{
  "jsonrpc": "2.0",
  "result": {
    "iconmapids": [
      "1"
    ]
  },
  "id": 1
}
```

See also

- [Icon mapping](#)

Source

ClconMap::update() in *ui/include/classes/api/services/ClconMap.php*.

From:
<https://www.zabbix.com/documentation/current/> - **Zabbix Documentation 5.0**

Permanent link:
<https://www.zabbix.com/documentation/current/manual/api/reference/iconmap/update>

Last update: **2020/05/05 09:17**

