

service.create

Description

object service.create(object/array **services**)

This method allows to create new services.

Parameters

(object/array) services to create.

Additionally to the [standard service properties](#), the method accepts the following parameters.

Parameter	Type	Description
dependencies	array	Service dependencies . Each service dependency has the following parameters: - dependsOnServiceid - (<i>string</i>) ID of an service the service depends on, that is, the child service. - soft - (<i>integer</i>) type of service dependency.
parentid	string	ID of a hard-linked parent service.
times	array	Service times to be created for the service.

Return values

(object) Returns an object containing the IDs of the created services under the `serviceids` property. The order of the returned IDs matches the order of the passed services.

Examples

Creating an service

Create an service that will be switched to problem state, if at least one child has a problem. SLA calculation will be on and the minimum acceptable SLA is 99.99%.

Request:

```
{
  "jsonrpc": "2.0",
  "method": "service.create",
  "params": {
    "name": "Server 1",
    "algorithm": 1,
    "showsla": 1,
    "goodsla": 99.99,
  }
}
```

```
    "sortorder": 1
  },
  "auth": "038e1d7b1735c6a5436ee9eae095879e",
  "id": 1
}
```

Response:

```
{
  "jsonrpc": "2.0",
  "result": {
    "serviceids": [
      5
    ]
  },
  "id": 1
}
```

Source

CService::create() in *ui/include/classes/api/services/CService.php*.

From:

<https://www.zabbix.com/documentation/current/> - **Zabbix Documentation 5.0**

Permanent link:

<https://www.zabbix.com/documentation/current/manual/api/reference/service/create>

Last update: **2020/05/05 11:29**

