

user.create

Description

object `user.create(object/array users)`

This method allows to create new users.

Parameters

(object/array) Users to create.

Additionally to the [standard user properties](#), the method accepts the following parameters.

Parameter	Type	Description
passwd (required)	string	User's password. Can be omitted if user is added only to groups that have LDAP access.
usrgrps (required)	array	User groups to add the user to. The user groups must have the <code>usrgrpid</code> property defined.
<code>user_medias</code>	array	User media to be created.

Return values

(object) Returns an object containing the IDs of the created users under the `userids` property. The order of the returned IDs matches the order of the passed users.

Examples

Creating a user

Create a new user, add him to a user group and create a new media for him.

Request:

```
{
  "jsonrpc": "2.0",
  "method": "user.create",
  "params": {
    "alias": "John",
    "passwd": "Doe123",
    "usrgrps": [
      {
        "usrgrpid": "7"
      }
    ]
  }
}
```

```
    ],
    "user_medias": [
      {
        "mediatypeid": "1",
        "sendto": [
          "support@company.com"
        ],
        "active": 0,
        "severity": 63,
        "period": "1-7,00:00-24:00"
      }
    ]
  },
  "auth": "038e1d7b1735c6a5436ee9eae095879e",
  "id": 1
}
```

Response:

```
{
  "jsonrpc": "2.0",
  "result": {
    "userids": [
      "12"
    ]
  },
  "id": 1
}
```

See also

- [Media](#)
- [User group](#)

Source

`CUser::create()` in `ui/include/classes/api/services/CUser.php`.

From:

<https://www.zabbix.com/documentation/current/> - **Zabbix Documentation 5.0**

Permanent link:

<https://www.zabbix.com/documentation/current/manual/api/reference/user/create>

Last update: **2020/05/05 11:31**

